

## megol Motorenoel High Condition SAE 5W-40

megol Motorenoel High Condition SAE 5W-40 is a modern, low-viscosity quality engine oil for all-year use. It is sure to prevent deposit build-up, reduces friction loss in the engine and provides optimal wear protection. megol Motorenoel High Condition SAE 5W-40 therefore results in better fuel economy and an extended service life for the engine.

The instructions issued by the manufacturers are to be followed.

<b>Specifications and Approvals:</b>	ACEA A3/B4-08 API SM/CF Renault RN 0700 Renault RN 0710 Porsche A40 BMW Longlife-01 VW 502 00/ 505 00 Mercedes Benz 229.5
--------------------------------------	--

**Meguin also recommends this product for vehicles that are subject to the following specifications:**

Opel GM LL-B-025  
Fiat 9.55535-H2  
Fiat 9.55535-M2  
PSA B71 2294  
PSA B71 2296

<b>Characteristic data</b>	<b>approx. values</b>		
SAE viscosity class	DIN 51511		5W-40
Viscosity at -30 °C	DIN 51377	mPas	< 6.600
Viscosity at 40 °C	DIN 51562	mm <sup>2</sup> /s	90.0
Viscosity at 100 °C	DIN 51562	mm <sup>2</sup> /s	14.7
Viscosity index	DIN ISO 2909		171
Density at 15 °C	DIN 51757	kg/m <sup>3</sup>	855
Colour pursuant to ASTM	DIN 51578		L4,0
Flash point	DIN ISO 2592	°C	236
Pour point	DIN ISO 3016	°C	-33
Ash, sulphate	DIN 51575	g/100 g	1,2
Base number	DIN ISO 3771	mg KOH/g	9.5
Evaporation loss	DIN 51581	%-by-weight	10.0
High shear/ high temperature viscosity	ASTM D 4683	mPas	>3.5