



# MULTIPOWER PLUS 5W40

Gasoline Engine Oil

Technosynthese®

## TYPE OF USE

Designed for high performance engines (GASOLINE, LPG, turbocharged or atmospheric) in cold conditions.

Suitable for standard and unleaded fuel.  
All driving conditions : City, Road, Highway.

## PERFORMANCE

STANDARDS                      API SN

MULTIPOWER PLUS has been developed and tested in accordance with the latest performance specifications. It incorporates the latest lubricant technology to meet the current API SN performance.

The high performance anti-wear additive results in reduction of engine internal frictions and increases life duration by the wear reduction.  
Excellent anti-oxidation preventing premature oil thickening and ageing due to thermal stress,  
Very efficient anti-deposit and anti-black sludge power which maintains a clean engine.  
Anti-corrosion, Anti-foam properties.  
Excellent in cold climate conditions.

## RECOMENDATIONS

Drain interval : according to manufacturers' recommendations and tuned to your own use.

## PROPERTIES

Viscosity grade	SAE J 300	<b>5W-40</b>
Density at 15°C (68°F)	ASTM D4052	0.852
Viscosity at 40°C (104°F)	ASTM D445	87.2 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	14.4 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	172
TBN	ASTM D2896	6.47 mg KOH/g