

Product information



SUNOCO Synturo Xenon 5W40

Description Full synthetic engine oil, specially developed to meet the VW 505.01 specification.

Application

- where VW 505.01 (engines with pump diesel injectors) is prescribed.
- for all modern gasoline-, LPG- and diesel engines, equipped with DPF (diesel particulate filter) and/or SCR (selective catalytic reduction), for which an ACEA C3 and SAE 5W40 engine oil is prescribed.

Specifications

- API SM / CF
- ACEA C3 & A3 / B4
- BMW LongLife 04
- Ford WSS-M2C 917A
- MB-Approval 229.51
- Porsche
- VW 502.00 / 505.00 / 505.01
- GM Dexos 2

Properties

- mid SAP oil, which expands the lifetime of the emission control systems without having any influence on the performance.
- good fluidity at low temperatures for a better cold start.
- low friction and thus fuel-economy & better performance together with a low CO2 emission.
- the engine keeps internally very clean.
- high quality for an optimal and very stable engine performance.

Typical analysis :

Density at 15°C	0.858
Viscosity at 40°C / cSt	86
Viscosity at 100°C / cSt	14
Viscosity at -30°C / cP	6000
Viscosity index	160
Flash point °C	230
Pour point °C	-39
TBN mg KOH/g	7,2
HTHS viscosity / cP	3,7
Colour	3,0

All technical data is provided for reference only.

1 - 2011