

Q8 Moto SBK Racing 10W-50

Description

High performance synthetic engine oil for motorcycles with race proven technology compatible with wet clutch systems requiring JASO MA2, SAE 10W-50

Application

Extreme high performance for four stroke, synthetic motor bike engine oil for all riding conditions including off-road and endurance. Recommended for latest high performance, multi-valve engines with catalyst.

Specifications

- JASO MA2
- ACEA A3/B4
- API SM

Benefits

- High performance JASO MA2 clutch friction performance
- Superior engine performance at extreme riding conditions
- Excellent engine protection after cold starting
- Offers high oil film strength and thus limiting engine wear
- Synthetic year round engine lubricant
- Provides sustained high oil pressure
- Prevents formation of black sludge
- Low volatility by use of synthetic base oils provides minimized oil consumption
- Good protection against rust and corrosion
- Reduced environmental impact
- Catalyst compatible lubricant

Properties	Method	Unit	Typical
Viscosity Grade			SAE 10W-50
Absolute Density, 15 °C	D 1298	kg/m ³	857
Kinematic Viscosity, 40 °C	D 445	mm ² /s	119.2
Kinematic Viscosity, 100 °C	D 445	mm ² /s	17.6
Viscosity Index	D 2270	-	163
Flash Point	D 93	°C	215
Pour Point	D 97	°C	-39
Apparent Viscosity, -25 °C	IP 383	mPa.s	6310
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.