



H-TECH 100 4T

Oil for 4 stroke motorcycle engine

SAE 10W-40

100% Synthetic

TYPE OF USE

All 4 stroke motorbike engines

Road and off road bikes, Trails, 4 stroke Cross/Enduro bikes, Quads, Scooters, Mopeds...

PERFORMANCE

STANDARDS:

API SL
JASO MA



PRODUCT MEETING JASO T 903
COMPANY GUARANTEEING THIS MA
PERFORMANCE : MOTUL

JASO MA is a friction test for motorcycle 4 stroke engine oils which guarantees the perfect working of wet clutch and consequently the gearbox longevity.

Excellent anti-oxidation preventing premature oil thickening and ageing due to high temperature stress.
High lubricating properties which decrease friction and wear and increase engine life.
Excellent wet clutch performance.
High detergent and dispersive properties.
Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Oil change: according to manufacturers' requirements and to be adjusted according to particular use.
MOTUL H-Tech 100 4T can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 15°C (59°F)	ASTM D1298	0.856
Viscosity at 100°C (212°F)	ASTM D445	14.5 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	96.9 mm ² /s
Viscosity index	ASTM D2270	155
Flash Point	ASTM D92	230
TBN	ASTM D2896	7.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - FAX: 33 1 48 33 28 79 - Site Web : www.motul.fr

8419

1205