




# PRODUCT CATALOGUE





## SOLID BUSHING

CYC CHAINS only use solid bushing for every chain models. With seamless smooth surface and greater roundness, the solid bushing chains extend the wear life up to 2 times compare to curled bushing chains.



## CST PIN TREATMENT

CYC's CST pin treatment provides an optimal wear resistance for off road and racing use. Extremely hard outside coating increase strength and reduce chain waer. At the same time, soft inner core also offer superior impact and shock absorption.

## QUAD-PIN RIVETING

For additional strength and extra resistance against push-out forces.

## VX-RING

is especially designed for reducing friction resistance by smaller contact area. The shape of ring also offer better sealing performance than standard o-rings. VX-ring chain have the greatest wear resistance of any other type of o-ring or non o-ring chains.

## COLORFUL PLATE

For the colorful ! Every colors are available for CYC CHAINS models.



## TYPE OF CONNECTING LINK

LFC : Loose-fit Clip type  
 PFC : Press-fit Clip Type  
 PFR : Press-fit Riveted Type

# EVX SERIES



### ULTIMATE SUPERSPORT CHAIN

- VX-RING
- SUPERIOR WEARLIFE
- ULTIMATE TENSILE STRENGTH
- SOLID BUSHINGS
- HIGH FLEXIBILITY
- LOW MAINTENANCE

Chain No.	Seal Type	Pin Length mm	Roller Dia. mm	Plate Thickness		Tensile Strength		Weight		Disp. Max cc's		Conn. Link Option	
				Outer mm	Inner mm	kN	Lbs.	100 Links Kg	Lbs.	Street	Dirt	Standard	Optional
520EVX	VX	20.80	10.25	2.2	2.2	42.0	9,440	1.66	3.66	1,200	750	PFR	N/A
525EVX	VX	23.55	10.25	2.6	2.4	46.3	10,400	2.05	4.52	1,300	N/A	PFR	N/A
530EVX	VX	25.15	10.25	2.6	2.4	46.3	10,400	2.15	4.74	1,400	N/A	PFR	N/A

# SVX SERIES



## PRO STREET BIKE CHAIN

- VX-RING
- HIGH FLEXIBILITY
- OPTIMAL TENSILE STRENGTH
- SOLID BUSHINGS
- LOW MAINTENANCE
- HIGH C/P RATIO

Chain No.	Seal Type	Pin Length mm	Roller Dia. mm	Plate Thickness		Tensile Strength		Weight		Disp.		Conn. Link Option	
				Outer mm	Inner mm	kN	Lbs.	100 Links Kg	Lbs.	Max cc's Street	Dirt	Standard	Optional
520SVX	VX	20.00	10.25	2.0	2.0	38.2	8,590	1.55	3.42	1,000	750	PFR	PFC
525SVX	VX	22.35	10.25	2.2	2.2	42.0	9,440	1.87	4.12	1,000	750	PFR	PFC
530SVX	VX	23.95	10.25	2.2	2.2	42.0	9,440	1.97	4.34	1,000	750	PFR	N/A

# SVO SERIES



## QUALITY O-RING CHAIN

- O-RING
- GREAT CHAIN LIFE
- SOLID BUSHINGS

Chain No.	Seal Type	Pin Length mm	Roller Dia. mm	Plate Thickness		Tensile Strength		Weight		Disp.		Conn. Link Option	
				Outer mm	Inner mm	kN	Lbs.	100 Links Kg	Lbs.	Max cc's Street	Dirt	Standard	Optional
420SVO	0	16.35	7.77	1.5	1.5	20.2	4,540	0.76	1.68	100	100	PFC	LFC
428HSVO	0	18.50	8.51	1.8	1.8	23.8	5,350	1.03	2.27	125	80	PFC	PFR
520SVO	0	20.00	10.16	2.0	2.0	35.6	8,000	1.44	3.18	650	450	PFR	PFC
525SVO	0	22.35	10.16	2.2	2.2	38.2	8,590	1.82	4.01	750	650	PFR	N/A
530SVO	0	23.95	10.16	2.2	2.2	38.2	8,590	1.90	4.19	900	750	PFR	N/A

# CRM SERIES



## PROFESSIONAL MOTOCROSS CHAIN

- CST PIN TREATMENT
- ANTI-KINKING
- LIGHT WEIGHT DESIGN
- SOLID BUSHINGS
- LOW MAINTENANCE

Chain No.	Seal Type	Pin Length mm	Roller Dia. mm	Plate Thickness		Tensile Strength		Weight		Disp.		Conn. Link Option	
				Outer mm	Inner mm	kN	Lbs.	100 Links Kg	Lbs.	Max cc's Street	Dirt	Standard	Optional
415HCM3	-	13.30	7.70	1.5	1.5	20.0	4,495	0.70	1.54	125	85	LFC	PFC
420CRM3	-	14.80	7.70	1.5	1.5	20.2	4,540	0.73	1.61	N/A	100	LFC	PFC
428HCM3	-	17.30	8.51	1.8	1.8	24.8	5,575	0.88	1.94	N/A	200	LFC	PFC
520CRM4	-	17.70	10.25	2.0	2.0	38.2	8,590	1.48	3.26	250	500	LFC	PFC
520CRMX	VX	20.00	10.25	2.0	2.0	38.2	8,590	1.55	3.42	600	500	PFC	PFR

# SV SERIES



## STANDARD MOTORCYCLE CHAIN

- SOLID BUSHINGS

Chain No.	Seal Type	Pin Length mm	Roller Dia. mm	Plate Thickness		Tensile Strength		Weight		Disp.		Conn. Link Option	
				Outer mm	Inner mm	kN	Lbs.	100 Links Kg	Lbs.	Max cc's Street	Dirt	Standard	Optional
415HSV	-	13.30	7.77	1.5	1.5	20.0	4,495	0.70	1.54	80	80	LFC	N/A
420SV	-	14.80	7.77	1.5	1.5	20.2	4,540	0.73	1.61	80	80	LFC	N/A
428SV	-	16.40	8.51	1.5	1.5	20.2	4,540	0.85	1.87	100	80	LFC	N/A
428HSV	-	17.30	8.51	1.8	1.8	23.8	5,350	0.88	1.94	125	80	LFC	N/A
520SV	-	17.60	10.16	2.0	2.0	35.6	8,000	1.54	3.40	350	250	LFC	N/A
525SV	-	19.50	10.16	2.0	2.0	35.6	8,000	1.68	3.70	400	N/A	PFC	PFR
530SV	-	20.60	10.16	2.0	2.0	35.6	8,000	1.72	3.79	400	N/A	PFC	PFR

RANGE	CHAIN NO.	50	100	125	250	400	650	750	800	900	1000	1200	1300	1400	
SUPERSPORT	520EVX														
	525EVX														
	530EVX														
SUPERSPORT & STREET	520SVX														
	525SVX														
	530SVX														
STREET	420SV0														
	428HSV0														
	520SV0														
	525SV0														
	530SV0														
SUPERCROSS & MOTOCROSS	415HCRM3														
	420CRM3														
	428HCRM3														
	520CRM4														
	520CRMX														
STREET / STANDARD	415HSV														
	420SV														
	428SV														
	428HSV														
	520SV														
	525SV														
	530SV														

THE APPLICATION LISTED IN THIS TABLE ARE FOR REFERENCE ONLY.



CHAIN YI LI INDUSTRIAL CO., LTD.  
NO.399, SEC. 2, SHATIEN RD., TATU DIST.,  
TAICHUNG CITY 43252 TAIWAN  
TEL : +886-4-2699-7061  
FAX : +886-4-2699-7062  
WEB : WWW.CYCCHAIN.COM.TW  
E-MAIL : CYCCHAIN@MS23.HINET.NET